

## **Installation instructions**

Audi A4 (8W) 2016 ►

Audi A5 (8W) 2017 ►

Audi Q5 (80A) 2017 ▶

Pedal covers/footrest

**Audi Genuine Accessories®** 

Edition 01

## **Service**



### **Contents**

1	General notes	1
2	Scope of delivery and overview of components	2
3	Sequence of operations	5
3.1	Removing and installing the pedal covers on the accelerator, brake and clutch pedals (left-hand drive vehicles)	5
3.1.1	Removing the pedal covers	5
3.1.2	Manual gearboxes: Installing the pedal covers on the clutch, brake and accelerator pedals	5
3.1.3	Automatic gearboxes: Installing the pedal covers on the brake and accelerator pedals	6
3.2	Removing and installing the pedal covers on the accelerator, brake and clutch pedals (right-	
	hand drive vehicles)	7
3.2.1	Removing the pedal covers	7
3.2.2	Manual gearboxes: Attaching the pedal covers to the clutch, brake and accelerator pedals	7
3.2.3	Automatic gearboxes: Attaching the pedal covers to the brake and accelerator pedals	8
3.3	Removing and installing the footrest	9
3.3.1	Manual and automatic gearboxes: Removing the footrest (left-hand drive vehicles)	9
3.3.2	Manual and automatic gearboxes: Installing the footrest (left-hand drive vehicles)	10
3.3.3	Manual and automatic gearboxes: Removing the footrest (right-hand drive vehicles)	10
3.3.4	Manual and automatic gearboxes: Installing the footrest (right-hand drive vehicles)	10

#### General notes 1

Please read these instructions carefully and note the WARN-ING, Caution and Note descriptions before the "pedal covers/ footrest" is installed.

#### **∕!\ WARNING**

Text with this symbol contains information regarding safety and indicates potential accident and injury risks.

#### (!) Caution

Text with this symbol indicates the risk of damage to the vehicle.

### Note

Text with this symbol contains additional information.

The pages that follow contain all of the information (subject to technical change) required to install and remove the pedal covers used in the vehicle.

Incorrect installation can cause damage to the pedal covers.

#### WARNING

The pedal covers must be installed by a specialist work-

- ♦ If the pedal cover is not installed correctly, it may cause the accelerator pedal to jam, resulting in hazardous driving conditions — risk of accident.
- ♦ If the pedal cover on the brake or accelerator pedal is loose, it may slip off the pedal in an emergency situation — risk of accident.

Audi AG shall not accept responsibility in the event of failure to comply with these installation instructions.



# 2 Scope of delivery and overview of components

Applies only to the Audi A4 (8W) and Audi A5 (8W):

Pedal cover sets required:

Pedal covers (set) for left-hand drive manual gearboxes, with footrest 8W1.064.200.A

Units	Part number	Description
1	8W1.721.173.C	Brake pedal cover
1	8W1.721.173.B	Clutch pedal cover
1	8W0.721.173	Accelerator pedal cover
1	8W1.864.777.A	Footrest
1		Information sheet

## Pedal covers (set) for left-hand drive automatic gearboxes, with footrest 8W1.064.205.A

Units	Part number	Description
1	8W1.723.173.A	Brake pedal cover
1	8W0.721.173	Accelerator pedal cover
1	8W1.864.777.A	Footrest
1		Information sheet

## Pedal covers (set) for right-hand drive manual gearboxes, with footrest 8W2.064.200.A

Units	Part number	Description
1	8W2.721.173.C	Brake pedal cover
1	8W2.721.173.B	Clutch pedal cover
1	8W0.721.173	Accelerator pedal cover
1	8W2.864.777.A	Footrest
1		Information sheet


## Pedal covers (set) for right-hand drive automatic gearboxes, with footrest 8W2.064.205.A

Units	Part number	Description
1	8W2.723.173	Brake pedal cover
1	8W0.721.173	Accelerator pedal cover
1	8W2.864.777.A	Footrest
1		Information sheet

Applies to the Audi A4 (8W), Audi A5 (8W) and Q5 (80A):

Pedal cover sets required:

Pedal covers (set) for left-hand drive manual gearboxes, without footrest 8W1.064.200





Units	Part number	Description
1	8W1.721.173.C	Brake pedal cover
1	8W1.721.173.B	Clutch pedal cover
1	8W0.721.173	Accelerator pedal cover
1		Information sheet

## Pedal covers (set) for left-hand drive automatic gearboxes, without footrest 8W1.064.205

Units	Part number	Description
1	8W1.723.173.A	Brake pedal cover
1	8W0.721.173	Accelerator pedal cover
1		Information sheet

## Pedal covers (set) for right-hand drive manual gearboxes, without footrest 8W2.064.200

Units	Part number	Description
1	8W2.721.173.C	Brake pedal cover
1	8W2.721.173.B	Clutch pedal cover
1	8W0.721.173	Accelerator pedal cover
1		Information sheet

## Pedal covers (set) for right-hand drive automatic gearboxes, without footrest 8W2.064.205

Units	Part number	Description
1	8W2.723.173	Brake pedal cover
1	8W0.721.173	Accelerator pedal cover
1		Information sheet

#### Applies only to the Audi Q5 (80A):

Pedal cover sets required:

## Pedal covers (set) for left-hand drive manual gearboxes, with footrest 80B.064.200.A

Units	Part number	Description
1	8W1.721.173.C	Brake pedal cover
1	8W1.721.173.B	Clutch pedal cover
1	8W0.721.173	Accelerator pedal cover
1	80B.864.777.C	Footrest
1		Information sheet

Pedal covers (set) for left-hand drive automatic gearboxes, with footrest 80B.064.205.A



Installation instructions - Audi A4 (8W) 2016 ► Audi A5 (8W) 2017 ► Audi Q5 (80A) 2017 ► Pedal covers/footrest Edition 01

Units	Part number	Description
1	8W1.723.173.A	Brake pedal cover
1	8W0.721.173	Accelerator pedal cover
1	80B.864.777.C	Footrest
1		Information sheet

## Pedal covers (set) for right-hand drive manual gearboxes, with footrest 80C.064.200.A

Units	Part number	Description
1	8W2.721.173.C	Brake pedal cover
1	8W2.721.173.B	Clutch pedal cover
1	8W0.721.173	Accelerator pedal cover
1	80C.864.777.A	Footrest
1		Information sheet

## Pedal covers (set) for right-hand drive automatic gearboxes, with footrest 80C.064.205.A

Units	Part number	Description
1	8W2.723.173	Brake pedal cover
1	8W0.721.173	Accelerator pedal cover
1	80C.864.777.A	Footrest
1		Information sheet






#### 3 Sequence of operations

#### 3.1 Removing and installing the pedal covers on the accelerator, brake and clutch pedals (left-hand drive vehicles)

Special tools and workshop equipment required

- ◆ Cleaning solution D.009.401.04
- ◆ Removal wedge -3409-



◆ Dismantling tool -T40280-



#### 3.1.1 Removing the pedal covers

- Remove the pedal covers using the removal wedge -3409-.

#### Manual gearboxes: Installing the pedal covers on the clutch, brake and accelerator pedals

#### 

Under no circumstances use silicone spray or tyre mounting paste when installing the pedal covers.

It is best to use cleaning solution D.009.401.04 to clean the pedals and covers, as special rubber care products will cause the pedal cover surfaces to become slippery.


◆ Risk of accident caused by the driver's feet slipping from the pedal as well as the pedal cover becoming loose.



Edition 01

#### Clutch pedal

 Starting from underneath -in the direction of arrow A-, pull the pedal cover over the pedal -in the direction of arrow B-. Make sure that the outer guide part and the entire outer rubber lip is in the correct position on the pedal cover.



#### Brake pedal


 Starting from underneath -in the direction of arrow A-, pull the pedal cover over the pedal -in the direction of arrow B-. Make sure that the central guide parts are in the correct position on the pedal and the entire outer rubber lip is in the correct position on the pedal cover.




Use a mirror to check that the outer rubber lips are in the correct position. Do the same for the central guide parts on the pedals.

#### **Accelerator pedal**

 Starting from underneath -in the direction of arrow A-, pull the pedal cover over the pedal -in the direction of arrow B-. Make sure that the entire outer rubber lip is in the correct position on the pedal cover.





#### 3.1.3 Automatic gearboxes: Installing the pedal covers on the brake and accelerator pedals



#### **. WARNING**


Under no circumstances use silicone spray or tyre mounting paste when installing the pedal covers.

It is best to use cleaning solution D.009.401.04 to clean the pedals and covers, as special rubber care products will cause the pedal cover surfaces to become slippery.

♦ Risk of accident caused by the driver's feet slipping from the pedal as well as the pedal cover becoming loose.

#### Brake pedal

- Starting from underneath -in the direction of arrow A-, pull
  the pedal cover over the pedal -in the direction of arrow B-.
  Make sure that the central guide parts -C- are in the correct
  position on the pedal and the entire outer rubber lip is in the
  correct position on the pedal cover.
- Central guide parts must be clipped into the foot of the pedal
   -D-.




#### **Accelerator pedal**

Starting from underneath -in the direction of arrow A-, pull
the pedal cover over the pedal -in the direction of arrow B-.
Make sure that the entire outer rubber lip is in the correct position on the pedal cover.



Use a mirror to check that the outer rubber lips are in the correct position. Do the same for the central guide parts on the pedals.



# 3.2 Removing and installing the pedal covers on the accelerator, brake and clutch pedals (right-hand drive vehicles)

#### 3.2.1 Removing the pedal covers

Remove the pedal covers using the removal wedge -3409-.

# 3.2.2 Manual gearboxes: Attaching the pedal covers to the clutch, brake and accelerator pedals

#### **MARNING**

Under no circumstances use silicone spray or tyre mounting paste when installing the pedal covers.

It is best to use cleaning solution D.009.401.04 to clean the pedals and covers, as special rubber care products will cause the pedal cover surfaces to become slippery.


 Risk of accident caused by the driver's feet slipping from the pedal as well as the pedal cover becoming loose.



Edition 01


#### Clutch pedal

 Starting from underneath -in the direction of arrow A-, pull the pedal cover over the pedal -in the direction of arrow B-.
 Make sure that the outer guide part and the entire outer rubber lip is in the correct position on the pedal cover.



#### **Brake pedal**

Starting from underneath -in the direction of arrow A-, pull
the pedal cover over the pedal -in the direction of arrow B-.
Make sure that the central guide parts are in the correct position on the pedal and the entire outer rubber lip is in the
correct position on the pedal cover.




#### **Accelerator pedal**

Starting from underneath -in the direction of arrow A-, pull
the pedal cover over the pedal -in the direction of arrow B-.
Make sure that the entire outer rubber lip is in the correct position on the pedal cover.



Use a mirror to check that the outer rubber lips are in the correct position. Do the same for the central guide parts on the pedals.



## 3.2.3 Automatic gearboxes: Attaching the pedal covers to the brake and accelerator pedals



#### WARNING


Under no circumstances use silicone spray or tyre mounting paste when installing the pedal covers.

It is best to use cleaning solution D.009.401.04 to clean the pedals and covers, as special rubber care products will cause the pedal cover surfaces to become slippery.

◆ Risk of accident caused by the driver's feet slipping from the pedal as well as the pedal cover becoming loose.

#### Brake pedal

Starting from underneath -in the direction of arrow A-, pull
the pedal cover over the pedal -in the direction of arrow B-.
Make sure that the central guide parts -C- are in the correct
position and the entire outer rubber lip is in the correct position on the pedal cover.




#### **Accelerator pedal**

Starting from underneath -in the direction of arrow A-, pull
the pedal cover over the pedal -in the direction of arrow B-.
Make sure that the entire outer rubber lip is in the correct position on the pedal cover.

### Note

Use a mirror to check that the outer rubber lips are in the correct position. Do the same for the central guide parts on the pedals.



#### 3.3 Removing and installing the footrest


## 3.3.1 Manual and automatic gearboxes: Removing the footrest (left-hand drive vehicles)

 Remove the cover -2- for securing bolt -A- using the removal wedge -3409-.

#### (!) Caution

A seal, which must not be lost or damaged, is located on the cover.

- Press on the footrest -1- and remove securing bolt -A-.
- Lift the footrest -1- from the top and remove in the -direction of the arrow-.





## 3.3.2 Manual and automatic gearboxes: Installing the footrest (left-hand drive vehicles)

 Insert the bottom of the footrest -1- and press in the -direction of the arrow-.

Edition 01


#### Note

Make sure that the rubber seal for the fuse carrier is in the correct position.

- Press on the footrest -1- in the -direction of the arrow- and screw into place.
- Clip the cover -2- for the securing bolt -A- in place.

### Note

- ◆ Make sure the seal on the cover -2- is in the correct position.
- ◆ All of the retaining lugs on the cover -2- must be present.




## 3.3.3 Manual and automatic gearboxes: Removing the footrest (right-hand drive vehicles)

- Remove the floor mat from the vehicle.
- Starting from the bottom and working upwards, unclip the footrest -1- using the removal wedge -D- in the -direction of the arrow-.
- Remove the footrest -1-.

#### **MARNING**

Remove broken snap-on elements from the footrest using tweezers to make sure that the new footrest is in the correct position!



## 3.3.4 Manual and automatic gearboxes: Installing the footrest (right-hand drive vehicles)

- Position the footrest -1- in the -direction of the arrow-.
- Install the footrest -1- fully into the fixtures of the baseplate and press firmly in place.

